

1300A Series Micro Beacon



The **1300A Series Micro Beacon** is an evolution of the popular 300 Series that has been designed to add extra versatility to the Micro Beacon range. It is ideal for use in shallow water environments or operations in confined space.

In addition to its internal batteries, the 1300A Series Micro Beacon has an external connector that allows it to operate from a ROV 24V power supply.

Channel selection is via a USB adaptor cable.

Key Features

- AAE Sigma Spread Spectrum technology
- Rechargeable NiMH batteries
- USB PC connectivity via 5 pin connector
- Charging via USB with onboard charge indicator
- Easy channel configuration via Beacon Editor app
- Can operate from a 24V power supply
- Responder interface
- Legacy support for almost all industry USBL systems currently in use
- PRV –Pressure Release Valve (Auto)
- On/Off shorting link

Applications

- General purpose tracking and positioning applications
- Diver tracking
- Static and dynamic operations e.g. ROV, and sidescan sonar

Technical Specification

MODEL TYPES – PHYSICAL SPECIFICATION

Housing material; Hard anodised aluminium

	Beam Pattern	SPL	Survival Depth	Diameter	Length	Weight air/water
1319A	±90°	183dB	600m	52mm	298mm	999g/438g
1329A	±90°	183dB	600m	52mm	298mm	1200g/550g

1300A Series Micro Beacon Technical Specification

ELECTRICAL SPECIFICATION

Battery

Battery type Rechargeable; NiMH
Charge Time Computer USB port: 1319A: 8 hours. 1329A 16 hours
(Typical) Mains USB dedicated charger: 1319A 4.0 hours. 1329A 8 hours

Listening life 1319A 30 days minimum (at 2°C)
1329A 45 days minimum (at 2°C)

Operational life 1319A 30 hours at 1.0pps (AAE Spread Spectrum)
24 hours at 1.0pps (HiPAP / HPR400)
1329A 60 hours at 1.0pps (AAE Spread Spectrum)
48 hours at 1.0pps (HiPAP / HPR400)

Operational life reduced when used with non AAE channels and dependant on rate.

Configuration

Set-up AAE Beacon Editor software
Transmit frequency range 21.5 - 30.5kHz
Receive frequency range 16.0 - 26.5kHz
Turnaround time Dependent on channel selection
Transmit pulse width Dependent on channel selection

External Inputs

Connector type MCBH5M
USB interface USB 1.1/2.0 (driver required)
Responder key Positive 5-20 Volts
External Power/Charge 24 Volts @ 50mA
Ground Common ground
On/Off Via connector shorting link

USBL COMPATIBILITY

AAE Nexus
AAE Easytrak
AAE V-Nav
Kongsberg HPR/HiPAP
iXblue GAPS
Sonardyne USBL

OPTIONS

- Compatibility with USBL systems not listed above
- Remote transducer, supplied with model BCN-1310A electronic bottle and model types RM91S or RM91SR, omni-directional, depth rated to 1000m, complete with interconnect cable.



Due to continual product improvement, specification information may be subject to change without notice.
1300 Series Micro Beacon/April 2019
©Applied Acoustic Engineering Ltd.



Applied Acoustic Engineering Ltd
Marine House, Marine Park
Gapton Hall Road
Great Yarmouth NR31 0NB
United Kingdom

T +44(0)1493 440355
F +44(0)1493 440720
E general@appliedacoustics.com
W www.appliedacoustics.com