

Easytrak Nexus Lite, Model 2695




Key Features

- Bi-directional Sigma Spread Spectrum acoustics
- Full hemispherical tracking
- 8 target tracking
- Internal data logging
- USB connected console
- Optional graphical overlay
- Optional calibration software

Easytrak Nexus Lite is an advanced USBL positioning and tracking system that determines the position of dynamic subsea targets through the transmission and reception of acoustic signals between the submerged transceiver and a target beacon. It incorporates Sigma 1 Spread Spectrum technology to provide a secure acoustic link. By incorporating Sigma 1 technology the wide bandwidth transmissions reduce the system's susceptibility to interference.

Designed for ease of installation in a vessel's operations room, the surface console has been mounted within a rugged 1U enclosure for connection to a laptop or tablet PC.

Easytrak Nexus Lite retains legacy compatibility with tone beacons.



Optional geo-referenced graphical overlay

Technical Specification

EASYTRAK NEXUS LITE CONSOLE, MODEL EZT-2695 provides DC power, high speed digital communications to the transceiver with a USB interface to user PC running Easytrak Nexus Lite software.

Dimensions	1U, 254 x 54 x 260mm
Weight	1.0kg
Power requirements	48Vdc / Vac Adapter Input: 90Vac – 230Vac 47-63Hz typically 3A
Connection to transceiver	Rear panel connector for 2683 Transceiver
Temperature	Operating: -10° to +40°C Storage: -20° TO +50°C
Front panel indicators	LED indicators for power and serial status.
Serial communications	4 x Console RS-232 Data Ports. System utilises PC ports if available

2695 Nexus Lite Technical Specification

Data Output	AAE format V1 and V2, TP-II2EC, TP-EC W/PR, Simrad 300P, Simrad 309, Simrad \$PSIMSSB, Pseudo \$GPRMC, NMEA \$GPGGA, NMEA \$GPVTG, NMEA \$GPTLL, Pseudo \$GPGGA, KLEIN 3000 (Quick set) Multiple outputs available
Compass Input	SGB-HTDS, SGB-HTDt, NMEA HDT,HDM, HDG
VRU Input	TCM-2.X, \$HCXDR , TSS1
Calibration	Optional EasyCal 2 USBL Calibration tool.
GPS / DGPS Input	NMEA; GLL, GGA, RMC Optional Geo Referenced Graphical Overlay. GeoTiff, DXF
Target Heading Input	NMEA HDM, HDT, HDG, PNI TCM2
Target Depth Input	NMEA DBT, DBK, DBS, DPT, AAE
Time in	GPS Time synch
Responder Output	Positive 12V pulse 5ms long
Audio	Audible activity indicator

EASYTRAK TRANSCIVER, TYPE EZT-2683 Factory calibrated multi-element transceiver head complete with integral AHRS and temperature sensor.

Material	316 Stainless Steel
Weight in air/water	11kg/8.5kg
Dimensions	100mm x 500mm (Ø x L)
Temperature	Operating: -10° to +40°C Storage: -20° to +50°C
Depth rating	30m
Electrical supply	48Vdc
Temperature sensor	1° resolution between -10° and +40° C
Cable	30m standard (20-100m options) with connectors. 12.8mm Ø

ACCURACY/PERFORMANCE

Accuracy is based on the correct speed of sound being entered, no ray bending and an acceptable S/N ratio

Position accuracy	1.0% of slant range, with external sensors Acoustic accuracy excluding heading correction errors
Range resolution	Calculated to 0.1m resolution
Frequency band (MF)	18 - 30 kHz
Tracking beam pattern	Hemispherical, 180°
Transmitter	190dB re 1µPa at 1m
Integrated AHRS:	
Bearing resolution	0.1° displayed. Internally calculated to 0.01°
Heading sensor accuracy	0.8° rms standard; +/- 0.1° resolution/repeatability
Pitch/Roll sensor accuracy	+/- 0.20° rms +/- 0.1° resolution/repeatability
Beacon types	AAE Sigma 1 Digital Spread Spectrum and AAE Tone channels. AAE V-NAV channels. HPR 400 channels 1100, 1000, 1200A, 1300A Series Beacons, Digital Depth Transponders, AAE Release and Telemetry Beacons.
Interrogation rate	Internally set or external key
System	Externally assessed for immunity and emissions; conforms to 89/336/EEC. RoHS compliant



Due to continual product improvement specification information may be subject to change without notice.
Easytrak Nexus Lite Model 2695/Dec 2016
©Applied Acoustic Engineering Ltd.



Applied Acoustic Engineering Ltd
Marine House, Marine Park
Gapton Hall Road
Great Yarmouth NR31 0NB
United Kingdom

T +44(0)1493 440355
F +44(0)1493 440720
E general@appliedacoustics.com
W www.appliedacoustics.com